

RFID TAG INSTALLATION SYSTEM USING A VEHICLE AND METHOD THEREOF

BACKGROUND OF THE INVENTION

5

Field of the Invention

[0001] The present invention relates to a radio frequency identification (RFID) tag installation system using a vehicle and method thereof. RFID tag installation system of the present invention consists of a) two charge coupled device (CCD) cameras, b) two global positioning system (GPS) receivers, c) an inertial navigation system (INS), d) a distance measurement instrument (DMI), and e) an RFID tag writer and a tag installer. The system of the present invention acquires 3-
10 dimensional coordinates (position) and road information, and stores them in a RFID tag in real time or a post-processing stage and then, RFID tag is installed on the road.
15

Description of the Related Art

20 [0002] Generally, in the RFID technique, a radio frequency is used to check entrance of men and something, position and classification of groups. A conventional RFID system employs a reader, a tag and a computer or other equipment that can process data. The reader receives a specific data from the
25 tag, converts the data into a digital signal, verifies the converted digital signal and sends normal data to a computer or any other controller.

[0003] In the RFID technique, a user does not have to directly contact to a tag to recognize data or connect a connection cable to directly operate the conventional RFID system. It is the advantage of the RFID technique that such
5 direct manipulations are not required.

[0004] Since no nonmetallic bodies shield electromagnetic waves, the reader can read data on the tag without failure even though the tag is hidden in a body or by bodies.

[0005] The RFID tag is installed on the road to supply
10 driver's current position and road information to driver. Besides, the driver's position is sent for traffic situation analysis to the Traffic Control Center though wireless network installed in the vehicle.

[0006] Most of all, in order to input the position and road
15 information to the RFID tag and install the RFID tag on the road, a measurement process to obtain precise position information is performed. It requires a lot of manpower and time

20 SUMMARY OF THE INVENTION

[0007] Accordingly, the present invention is directed to an RFID tag installation system using a vehicle and method thereof that substantially obviates problem due to limitations and disadvantages of the related art.

25 [0008] It is an object of the present invention to provide an RFID tag installation system using a vehicle and method thereof, which make it possible to install a RFID tag by only

a few people in a short time. The RFID tag supplies precise position and road information. In order to realize the system and method of the present invention, used in the vehicle equipped with two CCD cameras, two GPS receivers, an INS, a DMI, an RFID tag writer and a tag installer. The vehicle obtains 3-dimensional coordinates and road information of RFID tag installed region in appearing images in real time, and stores them in a RFID tag to install the a RFID tag on the road.

[0009] Additional advantages, objects, and features of the invention will be set forth in part in the description which follows and in part will become apparent to those having ordinary skill in the art upon examination of the following or may be learned from practice of the invention. The objectives and other advantages of the invention may be realized and attained by the structure particularly pointed out in the written description and claims hereof as well as the appended drawings.

To achieve these objects and other advantages and in accordance with the purpose of the invention, as embodied and broadly described herein, the system includes: An RFID tag installation system using two CCD cameras, two GPS receivers, an INS, a DMI and a sensor synchronizer, being installed inside and outside of a vehicle, the system comprising:

a vehicle position(x, y, z) and yaw extractor by using the two GPS receivers;

an orientation(position, attitude) extractor for the

vehicle by using INS;

a GPS/INS/DMI integrator for GPS outage and for INS error correction in real time or in a post-processing stage;

a camera interior/exterior orientation extractor for
5 estimating lens distortion, focal length, principle point, and orientation of the CCD camera;

a target position extractor for finding 3-dimensional coordinates of a road in which the RFID tag is installed;

a road information storage for providing road information
10 such as a speed limit and a rout number of a road in which the RFID tag is installed;

a RFID tag writer for inputting 3-dimensional coordinates and road information to the RFID tag; and

a RFID tag installer for installing the RFID tag on the
15 road.

In another aspect of the present invention, in an RFID tag establishing method, a CCD camera, a GPS receiver, an INS, a DMI and a sensor synchronizer are used. The CCD camera, the GPS receiver, the INS and the DMI are installed inside and
20 outside a vehicle. The method includes the steps of: calculating orientation of the vehicle by using GPS/INS/DMI integration in real time or post-processing(a);

(b) while the step (a) is performed, extracting camera interior /exterior orientation by using self-calibration;

25 (c) finding 3-dimensional coordinates of a road in which the RFID tag is installed region by using camera interior/exterior orientation extracted at the step (b) , the

vehicle orientation obtained at the step(a), and target region appearing in stereo images;

(d) inputting the road information supplied from a road information storage and the location information found at the
5 step (c) to the RFID tag; and

(e) Installing the RFID tag on the road, the RFID tag receiving the 3-dimensional coordinates and the road information at the step (d).

[0010] It is to be understood that both the foregoing
10 general description and the following detailed description of the present invention are exemplary and explanatory and are intended to provide further explanation of the invention as claimed.

BRIEF DESCRIPTION OF THE DRAWINGS

15 [0011] The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a part of this application, illustrate embodiment(s) of the invention and together with the description serve to explain the principle of the
20 invention. In the drawings:

[0012] FIG. 1 illustrates architecture of an RFID tag installation system using a vehicle according to the present invention; and

[0013] FIG. 2 is a flowchart of an RFID tag installation
25 method using a vehicle according to the present invention.

DETAILED DESCRIPTION OF THE INVENTION

[0014] Reference will now be made in detail to the preferred embodiments of the present invention, examples of which are illustrated in the accompanying drawings. Wherever possible, the same reference numbers will be used throughout the drawings to refer to the same or like parts.

[0015] FIG. 1 illustrates architecture an RFID tag installation system using a vehicle according to the present invention.

[0016] Referring to FIG. 1, an RFID tag installation system is installed in a vehicle. The vehicle is equipped with two CCD cameras 104, two GPS receivers 101, an INS 102 and a DMI 103. The RFID tag installation system includes a vehicle position and yaw extractor 201, a GPS/INS/DMI integrator 202, two cameras interior/exterior orientation extractor 203, a target position extractor 204, a road information storage 302, an RFID tag writer 301, and an RFID tag installer 303.

[0017] The two CCD cameras 104 are installed outside the vehicle and supply image information of the RFID tag installed region. two GPS receivers 101 receive vehicle information such as position and yaw of the vehicle when the CCD camera 104 obtains image information. The INS 102 determines attitude (roll, pitch and yaw) of the vehicle when the CCD camera 104 obtains image information. The DMI 103 supplies correction information to the GPS receiver 101 and the INS 102 in case of GPS signal outage.

[0018] The vehicle position and yaw extractor 201

calculates vehicle information such as yaw, position and attitude of the vehicle by using the position information of the vehicle obtained by two GPS receivers. The GPS/INS/DMI integrator 202 integrates the GPS receiver 101, the INS 102
5 and the DMI 103, and provides the position and the attitude of the vehicle in real time or a post-processing stage with reference to the vehicle information supplied from the vehicle position and yaw extractor 201. The two cameras interior/exterior extractor 203 corrects camera distortion
10 information of original image information obtained by the CCD camera, calculates focal length, principle point, a position, and an attitude of the each CCD camera 104. The target region position extractor 204 finds 3-dimensional coordinates of the RFID tag installed region by using image information obtained
15 by the camera interior/exterior orientation extractor 203 and the vehicle information obtained by the GPS/INS/DMI integrator 202. The road information storage 302 stores road information such as speed limit and rout number of a road on which the RFID tag is installed. The RFID tag writer 301 inputs the
20 position information calculated by the target region position extractor 204 and the road information obtained by the road information storage 302 to the RFID tag. The RFID tag installer 303 installs the RFID tag on the road. The RFID tag receives the position information and the road information
25 from the RFID tag writer 301.

[0019] The RFID tag is attached to a screw, a nail or a reflection plate, receives the position and the road

information from the RFID tag writer 301, and installed on the road.

[0020] FIG. 2 is a flowchart of an RFID tag installation method using a vehicle according to the present invention.

5 Description will be made on a method for establishing an RFID tag by using a vehicle equipped with two CCD cameras, two GPS receivers, an INS, a DMI and a sensor synchronizer.

[0021] As described above, The position and attitude of moving RFID tag installation RFID tag installation system are
10 calculated.(S100).

[0022] At the same time, the interior/exterior orientation of the each CCD camera are calculated by camera self-calibration method (S200).

[0023] Then, the orientation of each CCD camera of moving
15 RFID tag installation RFID tag installation system is estimated by combining position and attitude of CCD with GPS/INS/DMI data(S300).

[0024] Finds 3-dimensional position of the RFID tag installed region by using above parameters and stereo
20 images(S400).

[0025] The RFID tag is attached to a body such as a screw, a nail or a reflection plate installed by on the road(S500).

[0026] The 3-dimentional position and the road information are inputted by RFID writer.(S600).

25 [0027] It will be apparent to those skilled in the art that various modifications and variations can be made in the present invention. Thus, it is intended that the present

invention covers the modifications and variations of this invention provided they come within the scope of the appended claims and their equivalents.